



# JC371

## Multi-Channel AI DashCam

The JC371, designed specifically for commercial vehicles, is a powerful remote video monitoring terminal that supports up to 3 cameras and incorporates advanced visual AI algorithms like ADAS and DMS. Its built-in antenna system simplifies wiring, delivering enhanced economy, convenience, visibility, and intelligence to fleet managers.

The JC371 keeps tabs on following distance, lane keeping, and driver alertness, ensuring that drivers and fleet managers receive instant in-cab alerts for potential hazards, making the road safer. It also has emergency alert features like a panic button and uploads relevant video clips to the cloud for storage.

A comprehensive management solution, the JC371 is perfect for managing commercial fleets in public transportation, logistics, hazardous materials, and ride-sharing services.



Logistics Service



Hazmat Trucking



Taxi Service



Online Ride-hailing



### Video Surveillance

Powerful LTE connectivity enables the live monitoring of the vehicle's interior and exterior via an online platform; while the critical video clips in the device allows for on-demand playback after the fact from anywhere, at any time.



### Multi-Channel Recording

Multiple cameras can be configured to monitor various angles, providing a fuller view of the vehicle and its surroundings.



### Visual AI Algorithms

The device uses a variety of AI algorithms, such as ADAS and DMS, to provide tools that help improve road safety and driver safety and compliance.



### Intelligent Positioning

Locate vehicles using GPS signals and collect location data, vehicle speed and other data for analysis.



### Multiple Alerts

Record and upload video clips or still images of customizable events such as speeding and SOS button activation.



### Vehicle Immobilization

Enable you to cut off the fuel/power to the vehicle moving under 20km/h using Tracksolid Pro, which is useful if your fleet vehicle has been stolen.



### Extension Interface

Various ports such as TTL provide support for optional accessories such as fuel and temperature sensors.



### Expanded Storage

The device has a highly-reliable 128GB EMMC memory and also supports memory expansion by adding a TF card.

# Specifications

## Cellular

<b>Technology</b>	4G LTE Cat 4, 3G (WCDMA), 2G (GSM)
	2G Network GPRS/EDGE 900/1800 MHZ
<b>Frequency</b>	3G Network WCDMA/HSDPA/HSUPA Band 1/5/8
	4G Network FDD LTE Band 1/3/5/7/8/20/28A/28B
	TDD LTE Band 38/40

## GNSS

<b>Positioning system</b>	GPS, AGPS
---------------------------	-----------

## Camera

<b>Camera support</b>	1080P x 3
<b>Video format</b>	.ts

## Power

<b>Input voltage</b>	DC 9–30V
----------------------	----------

## Operating environment

<b>Operating temperature</b>	–20°C to +70°C
<b>Storage temperature</b>	–30°C to +85°C

## Physical specification

<b>Dimensions</b>	114,0 x 113,0 x 33,0mm
<b>Weight</b>	294g

## Interface

<b>LED indication</b>	Red (Power), Blue (Cellular), Green (GNSS), White (AI)
<b>SIM</b>	Nano-SIM
<b>Internal memory</b>	EMMC 128GB
<b>External memory</b>	TF card (up to 256GB*1)
<b>USB</b>	Type-C
<b>WiFi</b>	2.4GHz, Support AP Mode/STD Mode/WIFI Direct
<b>Bluetooth</b>	N/A
<b>Microphone</b>	Support
<b>Speaker</b>	Support
<b>Digital I/Os</b>	2*SOS, 2*Relay, 2*Reserved inputs
<b>Analog I/Os</b>	N/A
<b>Serial ports</b>	2*TTL
<b>Sensor</b>	6-Axis accelerometer

## Feature

<b>ADAS</b>	FCW, HMW, LDW, PCW
<b>DMS (Optional)</b>	Phone use, Smoking, Distraction, Yawning, Eyes closed, No face detected
<b>Configuration support</b>	GPRS, SMS, Memory card, APP
<b>Firmware update</b>	USB Cable, Memory card, OTA
<b>Certification</b>	CE, FCC

## Standard Packing

<b>JC371 unit</b>	1	<b>Double-sided adhesive</b>	1
<b>Power cable</b>	1	<b>Screws</b>	3
<b>SOS button</b>	1	<b>Screwdriver</b>	1
<b>Mount base</b>	1		

## Optional Configuration\*

<b>Peripheral camera</b>	CI02: 1280x720/15FPS/F2.5/Color in daytime & mono in dim light/135° (HFOV)
	CI05F: 1920x1080/15FPS/F2.7/Color in daytime & mono in dim light/125.5° (HFOV)
	CI06F: 1920x1080/15FPS/F2.0/Color in daytime & mono in dim light/140° (HFOV)
	CI01: 1280x720/15FPS/F2.0/Color in daytime & mono in dim light/100° (HFOV)
	CI03: 1280x720/15FPS/F2.4/Color in daytime & mono in dim light/119° (HFOV)
	CI04: 1280x720/15FPS/F2.4/Color in daytime & mono in dim light/119° (HFOV)
	CD02: 1280x720/15FPS/F2.0/Monochrome/56° (HFOV)
	CE01: 1280x720/15FPS/F2.0/Full color/IP67/125° (HFOV)
<b>Relay</b>	CE02: 1280x720/15FPS/F2.0/Full color/IP67/111° (HFOV)
	12V or 24V

\*Optional Configuration required to be customized or purchased separately.